NSN 5962-01-244-4820

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-244-4820 **Body Length:** 0.358 inches **Body Width:** 0.358 inches **Body Height:** 0.100 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and w/clock and w/enable and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 10 input **Design Function And Quantity:** 8 flip-flop, d-type, clocked **Case Outline Source And Designator:** C-2 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 11.00 nanoseconds propagation delay time, low to high level output and 11.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5962-01-244-4820

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0