# NSN 5962-01-245-2081

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-245-2081

## **Body Length:**

Between 0.342 inches and 0.358 inches

# Body Width:

Between 0.342 inches and 0.358 inches

# **Body Height:**

Between 0.064 inches and 0.100 inches

## **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Electrostatic sensitive and bidirectional and w/enable and hermetically sealed

## Inclosure Configuration:

Leadless flat pack

#### Output Logic Form:

Complementary-metal oxide-semiconductor logic

#### **Input Circuit Pattern:**

10 input

## **Design Function And Quantity:**

8 transceiver

# Case Outline Source And Designator:

C-2 mil-m-38510

# **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

7.0 volts power source

#### **Time Rating Per Chacteristic:**

7.50 nanoseconds propagation delay time, low to high level output and 7.50 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

20 leadless

#### Shelf Life:

N/a

#### Unit Of Measure:

--

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0