Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-245-6293

Body Length:	
1.290 inches	
Body Width:	
0.610 inches	
Body Height:	
0.210 inches	
Maximum Power Dis	sipation Rating:
1.02 watts	
Operating Tempurat	ure Range:
-55.0/+125.0 degrees	celsius
Storage Tempurature	e Range:
-65.0/+150.0 degrees	celsius
Features Provided:	
Hermetically sealed a	nd burn in and programmable and schottky and w/active pull-up and 3-state output
Inclosure Material:	
Ceramic and glass	
Inclosure Configurat	ion:
Dual-in-line	
Output Logic Form:	
Transistor-transistor lo	ogic de la constante de la const
Input Circuit Pattern	
14 input	
Case Outline Source	And Designator:
D-3 mil-m-38510	
Time Rating Per Cha	cteristic:
100.00 nanoseconds	propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output	
Precious Material Ar	d Location:
Terminal surface optic	on gold
Precious Material:	
Gold	
Test Data Document	
96906-mil-std-883 sta	ndard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
Yes - demil/mli	
Fiig:	
A458a0	