# NSN 5962-01-246-3677

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-246-3677

## **Body Length:**

0.785 inches

## **Body Width:**

Between 0.220 inches and 0.310 inches

## **Body Height:**

0.185 inches

#### **Operating Tempurature Range:**

+0.0/+70.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

## **Features Provided:**

Hermetically sealed and burn in and monolithic and positive outputs

#### **Inclosure Material:**

Ceramic

#### **Inclosure Configuration:**

## Dual-in-line

#### **Input Circuit Pattern:**

Dual 1 input

## **Design Function And Quantity:**

2 driver, clock

## **Case Outline Source And Designator:**

D-1 mil-m-38510

## **Terminal Surface Treatment:**

Solder

## Voltage Rating And Type Per Characteristic:

22.0 volts power source

## **Time Rating Per Chacteristic:**

24.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level output

## **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

14 printed circuit

#### Shelf Life:

N/a

## Unit Of Measure:

---

## **Demilitarization:**

Yes - demil/mli

#### Fiig:

A458a0