NSN 5962-01-247-0921

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-247-0921 **Body Length:** 0.358 inches **Body Width:** 0.358 inches **Body Height:** 0.100 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and high speed and monolithic and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Input Circuit Pattern:** 6 input **Design Function And Quantity:** 4 driver, line differential **Case Outline Source And Designator:** C-2 mil-m-38510 **Current Rating Per Characteristic:** 20.00 microamperes forward current, nonrepetitive, peak total value absolute **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 7.0 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

Yes - demil/mli

Fiig:

A458a0