## NSN 5962-01-247-1548

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-247-1548

Body L	ength:
3.200 ir	iches
Body V	/idth:
0.800 ir	iches
Body H	eight:
0.140 ir	iches
Maxim	Im Power Dissipation Rating:
5.0 wat	S
Operat	ng Tempurature Range:
-55.0/+*	125.0 degrees celsius
Storage	e Tempurature Range:
-65.0/+	150.0 degrees celsius
Feature	es Provided:
Hermet	cally sealed and burn in and w/clock and electrostatic sensitive and bidirectional
Inclosu	re Material:
Cerami	
Inclosu	re Configuration:
Dual-in-	line
Output	Logic Form:
Transis	tor-transistor logic
Input C	ircuit Pattern:
44 inpu	t i i i i i i i i i i i i i i i i i i i
Design	Function And Quantity:
1 multip	lier
Termin	al Surface Treatment:
Solder	
Voltage	e Rating And Type Per Characteristic:
7.0 volt	s power source
Test Da	ata Document:
96906-r	nil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Termin	al Type And Quantity:
64 print	ed circuit
Shelf L	ife:
N/a	
Unit Of	Measure:
Demilit	arization:
Yes - de	emil/mli
Fiig:	
A458a0	