NSN 5962-01-247-6516

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-247-6516

Body Length:

Between 0.753 inches and 0.785 inches

Body Width:

Between 0.265 inches and 0.285 inches

Body Height:

Between 0.140 inches and 0.160 inches

Maximum Power Dissipation Rating:

880.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

1240-01-216-6331 integrated sigh

Features Provided:

High performance and high slew rate and low power and fast settling and dielectric isolated

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 amplifier, operational, general purpose

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

40.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0