NSN 5962-01-247-8352

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-247-8352

Body Length: 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1000.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **End Application:** 6660-01-153-1269 cloud height se **Features Provided:** Hermetically sealed and burn in and high speed and low power **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 8 input **Design Function And Quantity:** 1 converter, analog to digital **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.3 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli

NSN 5962-01-247-8352

Digital-linear Microcircuit - Page 2 of 2

Fiig: A458a0

