NSN 5962-01-248-1544

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-248-1544

Body Length:	
0.840 inches	
Body Width:	
Between 0.220 inches and 0.310 inches	
Body Height:	
0.140 inches	
Maximum Power Dissipation Rating:	
303.0 milliwatts	
Operating Tempurature Range:	
-55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
-65.0/+150.0 degrees celsius	
Features Provided:	
Programmable and monolithic and schottky and asynchronous and synchronous and w/reset	
Inclosure Material:	
Ceramic and glass	
Inclosure Configuration:	
Dual-in-line	
Output Logic Form:	
Transistor-transistor logic	
Input Circuit Pattern:	
8 input	
Design Function And Quantity:	
1 counter	
Case Outline Source And Designator:	
D-2 mil-m-38510	
Terminal Surface Treatment:	
Solder	
Voltage Rating And Type Per Characteristic:	
7.0 volts power source	
Test Data Document:	
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type	data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type d	lata on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Terminal Type And Quantity:	
16 printed circuit	
Specification Data:	
81349-mil-m-38510/344 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
 Demilitarization:	
Yes - demil/mli	

NSN 5962-01-248-1544

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

