

View Online at <https://aerobasegroup.com/nsn/5962-01-248-5685>

Body Length:

0.358 inches

Body Width:

0.358 inches

Body Height:

0.100 inches

Maximum Power Dissipation Rating:

30.5 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and electrostatic sensitive and low power and schottky and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, exclusive or

Case Outline Source And Designator:

C-2 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

17.00 nanoseconds propagation delay time, low to high level output and 17.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

20 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0