NSN 5962-01-248-5689

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-248-5689 **Body Length:** 0.390 inches **Body Width:** 0.260 inches **Body Height:** 0.085 inches **Maximum Power Dissipation Rating:** 46.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and expandable and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Diode-transistor logic **Input Circuit Pattern:** Dual 5 input **Design Function And Quantity:** 2 gate, nand **Case Outline Source And Designator:** F-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 8.0 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 14 flat leads **Specification Data:** 81349-mil-m-38510/30 government specification Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-248-5689

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0