## NSN 5962-01-248-7304

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-248-7304 **Body Length:** 0.358 inches **Body Width:** 0.358 inches **Body Height:** 0.080 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Aircraft, f-16; aircraft, galaxy c-5 **Features Provided:** Electrostatic sensitive and hermetically sealed and burn in and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Triple 3 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 3 gate, nand **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 4.50 nanoseconds propagation delay time, low to high level output and 5.00 nanoseconds propagation delay time, high to low level output **Special Features:** Weapon system essential **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 leadless

**Unit Of Measure:** 

Shelf Life:

N/a

## NSN 5962-01-248-7304

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0