NSN 5962-01-248-8632

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-248-8632
Overall Length:
1.060 inches
Overall Height:
0.400 inches
Overall Width:
0.320 inches
Body Length:
1.060 inches
Body Width:
0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
149.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Bipolar and burn in and cascadable and low power and monolithic and schottky and w/clear
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Octal 3 input
Design Function And Quantity:
8 flip-flop, clocked, parallel gated
Case Outline Source And Designator:
D-8 mil-m-38510
Time Rating Per Chacteristic:
20.00 nanoseconds propagation delay time, low to high level output and 20.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-38510/325 government specification
Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-248-8632

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0