## NSN 5962-01-249-1120

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-249-1120

3
Body Length:
0.785 inches
Body Width:
0.260 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and w/enable and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
9 input
Criticality Code Justification:
Zzzy
Design Function And Quantity:
1 encoder, priority
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
20.0 volts power source
Time Rating Per Chacteristic:
440.00 nanoseconds propagation delay time, low to high level output and 440.00 nanoseconds propagation delay time, high to low level
output
Special Features:
Item must comply with requirements of defense supply center columbus production standard lo3629
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing

Shelf Life:

and testing specifications available at the dla icp

N/a

## NSN 5962-01-249-1120

Digital Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0