## NSN 5962-01-249-4638

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-249-4638 **Overall Height:** Between 0.290 inches and 0.380 inches **Overall Width:** Between 0.300 inches and 0.395 inches **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** 0.302 inches **Body Height:** Between 0.145 inches and 0.175 inches **Maximum Power Dissipation Rating:** 614.4 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Burn in and bipolar and hermetically sealed and schottky and programmable and 3-state output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Memory Device Type:** Rom **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5962-01-249-4638

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0