# NSN 5962-01-249-4949

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-249-4949

#### **Body Outside Diameter:**

Between 0.335 inches and 0.370 inches

#### **Body Height:**

Between 0.165 inches and 0.185 inches

## Maximum Power Dissipation Rating:

500.0 milliwatts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and monolithic

#### Inclosure Material:

Metal

#### Inclosure Configuration:

# Can

Input Circuit Pattern:

1 input

#### **Criticality Code Justification:**

Feat

#### **Design Function And Quantity:**

1 converter, voltage to frequency

#### Case Outline Source And Designator:

To-99 joint electron device engineering council

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

22.0 volts power source

#### **Special Features:**

Item must comply with requirements of defense electronics supply center production standard no. L03632; for navy nuclear propulsion plant products only

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### Terminal Type And Quantity:

8 pin

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

#### Fiig:

A458a0