NSN 5962-01-249-4951

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-249-4951

Body Length:
Between 0.753 inches and 0.785 inches
Body Width:
Between 0.265 inches and 0.285 inches
Body Height:
Between 0.140 inches and 0.170 inches
Maximum Power Dissipation Rating:
870.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
High speed and high slew rate and monolithic and wideband
Inclosure Material:
Ceramic and glass
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
2 input
Criticality Code Justification:
Zzzy
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
35.0 volts power source
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo3634
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
14 printed circuit
Reference Number Differentiating Characteristics:
Areference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing
and testing specifications available at the dla icp
Shelf Life:
N/a
Unit Of Measure:

Demilitarization: Yes - demil/mli

NSN 5962-01-249-4951

Linear Microcircuit - Page 2 of 2



Fiig:

A458a0