## NSN 5962-01-249-9214

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-249-9214 **Body Length:** 0.405 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and precision and monolithic and w/resistor **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 amplifier, operational, general purpose **Case Outline Source And Designator:** D-4 mil-m-38510 **Terminal Surface Treatment:** Gold or solder or tin **Time Rating Per Chacteristic:** 340.00 nanoseconds propagation delay time, low to high level output and 340.00 nanoseconds propagation delay time, high to low level output **Unpackaged Unit Weight:** 1.0 grams **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a **Unit Of Measure:** 

Fiig:

A458a0

**Demilitarization:** Yes - demil/mli