## NSN 5962-01-250-1659



Digital-linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-250-1659 **Body Length:** 0.395 inches **Body Width:** 0.287 inches **Body Height:** 0.067 inches **Maximum Power Dissipation Rating:** 1200.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and hermetically sealed and burn in and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 3 input and 8 channel **Design Function And Quantity:** 2 switch, analog **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 40.0 volts power source **Time Rating Per Chacteristic:** 1500.00 nanoseconds propagation delay time, low to high level output and 1500.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 flat leads Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Yes - demil/mli

Fiig:

A458a0