NSN 5962-01-250-5838

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-250-5838

view Offilite at https://aerobasegroup.com/hsi//0302-01-230-3030
Body Length:
1.280 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
0.185 inches
Maximum Power Dissipation Rating:
22.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and 3-state output and w/clear and low power and w/clock and schottky
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
Dual 7 input
Design Function And Quantity:
2 flip-flop, d-type, clocked
Case Outline Source And Designator:
D-9 mil-m-38510
Current Rating Per Characteristic:
21.00 milliamperes supply
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
15.00 nanoseconds propagation delay time, low to high level output and 22.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a

--

Unit Of Measure:

NSN 5962-01-250-5838

Digital Microcircuit - Page 2 of 2



_					
11	em)	 tor	172	n	

No

Fiig:

A458a0