NSN 5962-01-250-6209

Linear Microcircuit - Page 1 of 1

Body Length:



View Online at https://aerobasegroup.com/nsn/5962-01-250-6209

0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and high speed and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 2 input **Design Function And Quantity:** 1 comparator, voltage **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 12.00 nanoseconds propagation delay time, low to high level output and 6.50 nanoseconds propagation delay time, high to low level output **Test Data Document:** 14933-86008 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli Fiig: A458a0