NSN 5962-01-250-6931

Digital Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-250-6931
Body Length:
0.785 inches
Body Width:
0.291 inches
Body Height:
0.180 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
5865-01-076-9050 control receive
Features Provided:
Hermetically sealed and burn in and w/clock and low power and w/buffered output
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Design Function And Quantity:
1 shift register, static
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
18.0 volts power source
Time Rating Per Chacteristic:
600.00 nanoseconds propagation delay time, low to high level output and 600.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli