## NSN 5962-01-251-0528



Linear Microcircuit - Page 1 of 1		Group
View Online at https://aerobasegroup.com/nsn/5962-01-251-0528		
Body Length:		
1.130 inches		
Body Width:		
1.130 inches		
Body Height:		
0.500 inches		
Maximum Power Dissipation Rating:		
400.0 milliwatts		
Operating Tempurature Range:		
-55.0/+125.0 degrees celsius		
Storage Tempurature Range:		
-65.0/+150.0 degrees celsius		
End Application:		
4935-00-930-7250 test station, gu		
Features Provided:		
Hermetically sealed and burn in and monolithic and positive outputs		
Inclosure Material:		
Ceramic and metal		
Inclosure Configuration:		
Dual-in-line		
Input Circuit Pattern:		
2 input		
Design Function And Quantity:		
1 amplifier, operational, general purpose		
Terminal Surface Treatment:		
Solder		
Voltage Rating And Type Per Characteristic:		
22.0 volts power source		
Time Rating Per Chacteristic:		
800.00 nanoseconds propagation delay time, low to high level output and 800.00 nanoseconds propagation delay	/ time, high to le	ow level
output		
Test Data Document:		
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).		
Terminal Type And Quantity:		
7 printed circuit		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
Yes - demil/mli		

Fiig: A458a0