

View Online at <https://aerobasegroup.com/nsn/5962-01-251-7080>

Body Length:

Between 0.355 inches and 0.400 inches

Body Width:

Between 0.245 inches and 0.280 inches

Body Height:

0.172 inches

Maximum Power Dissipation Rating:

800.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

5811-01-162-2449 power supply

Features Provided:

Hermetically sealed and medium speed and high voltage and high current

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 driver, lamp

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Time Rating Per Characteristic:

65.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

8 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0