NSN 5962-01-251-8920



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-251-8920 **Body Length:** 0.440 inches **Body Width:** Between 0.245 inches and 0.285 inches **Body Height:** 0.085 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and w/enable and hermetically sealed and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Flat pack **Output Logic Form: Emitter-coupled logic Input Circuit Pattern:** 9 input **Design Function And Quantity:** 4 gate, exclusive or **Case Outline Source And Designator:** F-5 mil-m-38510 **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** -8.0 volts power source **Time Rating Per Chacteristic:** 5.50 nanoseconds propagation delay time, low to high level output and 5.50 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-251-8920

Digital Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0