## NSN 5962-01-252-3514

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-252-3514

| Body Length:   |
|--|
| 0.785 inches   |
| Body Width:  |
| Between 0.220 inches and 0.310 inches  |
| Body Height:   |
| 0.140 inches   |
| Maximum Power Dissipation Rating:  |
| 200.0 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+175.0 degrees celsius   |
| Features Provided:   |
| Hermetically sealed and electrostatic sensitive and monolithic   |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Output Logic Form:   |
| Complementary-metal oxide-semiconductor logic  |
| Input Circuit Pattern:   |
| Quad 2 input   |
| Criticality Code Justification:  |
| Feat   |
| Design Function And Quantity:  |
| 4 gate, nor  |
| Case Outline Source And Designator:  |
| D-1 mil-m-38510  |
| Terminal Surface Treatment:  |
| Gold and solder  |
| Voltage Rating And Type Per Characteristic:  |
| 18.0 volts power source  |
| Time Rating Per Chacteristic:  |
| 315.00 nanoseconds propagation delay time, low to high level output and 315.00 nanoseconds propagation delay time, high to low level |
| output   |
| Special Features:  |
| Itemmust comply with requirements of defense supply center columbus production standard no l03663; for navy irpod only               |
| Precious Material And Location:  |
| Terminal surfaces option gold  |

## Test Data Document:

**Precious Material:** 

Gold

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## NSN 5962-01-252-3514

Digital Microcircuit - Page 2 of 2



| Termin | al T | ne A  | nd O  | uantity: |
|--------|------|-------|-------|----------|
|        | aı ı | vuc r | uiu u | tuannıv. |

14 printed circuit

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0