

View Online at <https://aerobasegroup.com/nsn/5962-01-252-8282>

Body Length:

0.390 inches

Body Width:

0.260 inches

Body Height:

0.085 inches

Maximum Power Dissipation Rating:

750.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and positive outputs

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

Dual 1 input and dual 2 channel

Design Function And Quantity:

2 switch, analog, single pole double throw

Case Outline Source And Designator:

F-2 mil-m-38510

Terminal Surface Treatment:

Gold or solder or tin

Time Rating Per Characteristic:

290.00 nanoseconds propagation delay time, low to high level output and 360.00 nanoseconds propagation delay time, high to low level output

Precious Material And Location:

Terminal surface option gold

Precious Material:

Gold

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0