NSN 5962-01-253-0161

Memory Microcircuit - Page 1 of 2

Unit Of Measure:



View Online at https://aerobasegroup.com/nsn/5962-01-253-0161

Body Length:	
1.290 inches	
Body Width:	
Between 0.500 inches and 0.610 inches	
Body Height:	
0.150 inches	
Maximum Power Dissipation Rating:	
1.02 watts	
Operating Tempurature Range:	
55.0/+125.0 degrees celsius	
Storage Tempurature Range:	
65.0/+150.0 degrees celsius	
End Application:	
Radar set an/sps-4 (v) 5	
Features Provided:	
Programmable and hermetically sealed and monolithic and bipolar and 3-state output and high impedance	
nclosure Material:	
Ceramic and glass	
nclosure Configuration:	
Dual-in-line	
Dutput Logic Form:	
ransistor-transistor logic	
nput Circuit Pattern:	
14 input	
Case Outline Source And Designator:	
D-3 mil-m-38510	
Ferminal Surface Treatment:	
Solder	
/oltage Rating And Type Per Characteristic:	
7.0 volts power source	
Time Rating Per Chacteristic:	
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low	level
output	
Memory Device Type:	
Rom	
Test Data Document:	
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).	
Terminal Type And Quantity:	
24 printed circuit	
Shelf Life:	
N/a	

NSN 5962-01-253-0161

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

