

View Online at <https://aerobasegroup.com/nsn/5962-01-255-2497>

**Overall Length:**

Between 0.935 inches and 0.970 inches

**Overall Height:**

Between 0.155 inches and 0.280 inches

**Overall Width:**

Between 0.290 inches and 0.320 inches

**Body Length:**

Between 0.935 inches and 0.970 inches

**Body Width:**

Between 0.245 inches and 0.285 inches

**Body Height:**

Between 0.125 inches and 0.160 inches

**Operating Temperature Range:**

-0.0/+75.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and electrostatic sensitive and programmable

**Inclosure Material:**

Ceramic or metal

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

7 input

**Design Function And Quantity:**

1 array, logic

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

20 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0