# NSN 5962-01-255-2497

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-255-2497

### **Overall Length:**

Between 0.935 inches and 0.970 inches

## **Overall Height:**

Between 0.155 inches and 0.280 inches

## **Overall Width:**

Between 0.290 inches and 0.320 inches

#### **Body Length:**

Between 0.935 inches and 0.970 inches

#### **Body Width:**

Between 0.245 inches and 0.285 inches

#### **Body Height:**

Between 0.125 inches and 0.160 inches

#### **Operating Tempurature Range:**

-0.0/+75.0 degrees celsius

#### Storage Tempurature Range:

-65.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and electrostatic sensitive and programmable

#### **Inclosure Material:**

Ceramic or metal

## Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Transistor-transistor logic

#### Input Circuit Pattern:

7 input

#### **Design Function And Quantity:**

1 array, logic

#### **Terminal Surface Treatment:**

Solder

# Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

## Time Rating Per Chacteristic:

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

# Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

# Terminal Type And Quantity:

20 printed circuit

## Shelf Life:

N/a

# Unit Of Measure:

# NSN 5962-01-255-2497

Digital Microcircuit - Page 2 of 2

# Demilitarization:

Yes - demil/mli

Fiig:

A458a0

