## NSN 5962-01-256-1597

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-256-1597 **Body Length:** 1.485 inches **Body Width:** 0.600 inches **Body Height:** 0.205 inches **Maximum Power Dissipation Rating:** 790.0 milliwatts **Operating Tempurature Range:** +0.0/+75.0 degrees celsius Storage Tempurature Range: -65.0/+125.0 degrees celsius **End Application:** Wsd: aircraft, stratolifter c-135; aircraft, f-16; support equipment, b-1 aircraft **Features Provided:** Hermetically sealed and ultraviolet erasable and programmable and w/enable and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 16 input **Criticality Code Justification:** Feat **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Special Features:** 

N/a

Weapon system essential **Terminal Type And Quantity:** 

28 printed circuit

Shelf Life:

## NSN 5962-01-256-1597

Memory Microcircuit - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0