NSN 5962-01-256-3188

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-256-3188 **Body Length:** 0.870 inches **Body Width:** 0.290 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 750.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 5840-01-020-5631 radar set **Features Provided:** Hermetically sealed and burn in and bipolar and programmable and 3-state output and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 105.00 nanoseconds propagation delay time, low to high level output and 105.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

N/a

Terminal Type And Quantity:

16 printed circuit

Unit Of Measure:

Shelf Life:

NSN 5962-01-256-3188

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0