NSN 5962-01-256-4219

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-256-4219

| View Online at https://aerobasegroup.com/nsn/5962-01-256-4219 |
|--|
| Body Length: |
| Between 1.440 inches and 1.500 inches |
| Body Width: |
| Between 0.510 inches and 0.550 inches |
| Body Height: |
| Between 0.135 inches and 0.165 inches |
| Operating Tempurature Range: |
| -0.0/+70.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| End Application: |
| Console, display control oj-535v2/3 |
| Features Provided: |
| Programmable and ultraviolet erasable and electrostatic sensitive |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Output Logic Form: |
| N-type metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 16 input |
| Time Rating Per Chacteristic: |
| 250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level |
| output |
| Precious Material And Location: |
| Terminal surfaces option gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Demilitarination. |
| Demilitarization: Yes demilimit |
| Yes - demil/mli |
| Fiig: |

A458a0