## NSN 5962-01-256-6058

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-256-6058

**Overall Width:** 

Between 0.740 inches and 1.020 inches

**Body Length:** 

0.290 inches

**Body Width:** 

Between 0.240 inches and 0.260 inches

**Body Height:** 

Between 0.030 inches and 0.085 inches

**Maximum Power Dissipation Rating:** 

330.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

**Storage Tempurature Range:** 

-65.0/+150.0 degrees celsius

**Features Provided:** 

Burn in and monolithic and hermetically sealed

**Inclosure Material:** 

Ceramic

**Inclosure Configuration:** 

Flat pack

**Input Circuit Pattern:** 

2 input

**Design Function And Quantity:** 

1 comparator, voltage and 1 buffer

**Case Outline Source And Designator:** 

F-4 mil-m-38510

**Current Rating Per Characteristic:** 

50.00 milliamperes forward current, peak total value not applicable

**Terminal Surface Treatment:** 

Solder

Voltage Rating And Type Per Characteristic:

30.0 volts total supply

**Test Data Document:** 

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:** 

10 flat leads

**Specification Data:** 

81349-mil-m-38510/103 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

## NSN 5962-01-256-6058

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0