NSN 5962-01-256-6765

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-256-6765 **Body Length:** 1.290 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1.02 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** 4935-01-136-0233 shop equipment, **Features Provided:** Hermetically sealed and burn in and programmable and schottky and w/active pull-up and 3-state output **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 13 input **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 90.00 nanoseconds propagation delay time, low to high level output and 90.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

NSN 5962-01-256-6765

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0