## NSN 5962-01-256-8903

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-256-8903

1.1 waits         Operating Tempurature Range:         -55.0 to 125.0 degrees celsius         Storage Tempurature Range:         -65.0 to 125.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and thick film and hybrid         Inclosure Material:         Metal         Inclosure Configuration:         Dual-in-line         Output Logic Form:         Transistor-transistor logic         Input Circuit Pattern:         12 input         Design Function And Quantity:         1 converter, digital to analog         Terminal Surface Treatment:         Gold         Voltage Rating And Type Per Characteristic:         18.0 volts power source         Precious Material:         Gold         Duprinted cincuit         Spo	
Body Width: 1.200 inches Body Width: 1.200 inches Body Width: 1.200 inches Body Height: 0.250 inches Maximum Power Dissipation Rating: 1.1 watts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -56.0 to 125.0 degrees celsius Estorage Configuration: Inclosure Estorage Configuration: Inclosure Estorage Configuration: Inclosure Estorage Configuration: Inclosure Estorage Configuration: Inclosure Sourea Precious Material And Location: Terminal and case surfaces gold Precious Material: Biolo Utits Pocument: Biolo Utits Pocument: Biolo Utits Pocument: Biolo Utits Pocument: Biolo Utits Defined Contin Estorage Concente: Biolo Utits Distorage Concente: Biolo	
1.200 inches         Body Height:         0.250 inches         Maximu Power Dissipation Rating:         1.1 watts         Operating Tempurature Range:         -55.0 to 125.0 degrees celsius         Storage Tempurature Range:         -55.0 to 125.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and thick film and hybrid         Inclosure Material:         Metal         Inclosure Configuration:         Dual-in-line         Output Logic Form:         Transistor-transistor logic         Input Circuit Pattern:         12 input         Design Function And Quantity:         1 converter, digital to analog         Terminal Surface Treatment:         Gold         Voltage Rating And Type Per Characteristic:         18.0 volts power source         Precious Material:         Gold          Precious Material:         9006-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).         Terminal Type And Quantity:         30 printed circuit         Sheft Life:         Na         Unit Of Measure:         Low Count <t< td=""><td></td></t<>	
Body Height: 0.250 inches 0.250 inches Maximum Power Dissipation Rating: 1.1 watis Operating Tempurature Range: -50.0 to 125.0 degrees celsius Storage Tempurature Range: -50.0 to 125.0 degrees celsius Storage Tempurature Range: -60.0 to 125.0 degrees celsius Features Provided: Hermetically sealed and burn in and thick film and hybrid Inclosure Material: Metal Inclosure Material: Metal Inclosure Configuration: Dual-in-line Output Logic Form: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material: Metal Storage Rating And Type Per Characteristic: 18.0 volts power source Precious Material Motion Terminal and case surfaces gold Precious Material: 19906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Sheft Life: Na	-
0.250 inches Maximum Power Dissipation Rating: 1.1 watts Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 125.0 degrees celsius Features Provided: Hermetically sealed and burn in and thick film and hybrid Inclosure Material: Metal Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material: Gold Test Data Document Gold Test Data Document Gold Test Data Document: Gold Test Data Documen	
Maximum Power Dissipation Rating:         1.1 watts         Operating Tempurature Range:         -55.0 to 125.0 degrees celsius         Storag Tempurature Range:         -68.0 to 125.0 degrees celsius         Features Provided:         Hemetically sealed and burn in and thick film and hybrid         Inclosure Material:         Metal         Inclosure Configuration:         Dual-in-line         Output Logic Form:         Transistor-transistor logic         Input Circuit Pattern:         12 input         Design Function And Quantity:         1 converter, digital to analog         Terminal Surface Treatment:         Gold         Voltage Rating And Type Per Characteristic:         18.0 volts power source         Precious Material:         Gold	
1.1 waits Operating Tempurature Range: -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 125.0 degrees celsius Features Provided: Hermetically sealed and burn in and thick film and hybrid Inclosure Material: Metal Inclosure Material: Metal Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material: Gold Tercious Material: Tercious Material: Tercious Material: Tercious Material: Tercious Material: Tercious Material: Tercious Materi	
Operating Tempurature Range:         -55.0 to 125.0 degrees celsius         Storage Tempurature Range:         -65.0 to 125.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and thick film and hybrid         Inclosure Material:         Metal         Inclosure Configuration:         Dual-in-line         Output Legic Form:         Transistor-transistor logic         Input Oricruit Pattern:         12 input         Design Function And Quantity:         1 converter, digital to analog         Terminal Surface Treatment:         Gold         Voltage Rating And Type Per Characteristic:         13.0 volts power source         Precious Material And Location:         Terminal and case surfaces gold         Precious Material:         Gold         Voltage Rating And Type Per Characteristic:         13.0 volts power source         Precious Material And Location:         Terminal and case surfaces gold         Precious Material         Gold         Voltage Countert:         Gold         Supoin-inst-d-883 standard (includes industry or association standards, individual manufactureer standards, etc.).         Terminal Ty	Maximum Power Dissipation Rating:
So. U 125.0 degrees celsius Storage Tempurature Range: -65.0 to 125.0 degrees celsius Features Provided: Hermetically sealed and burn in and thick film and hybrid Inclosure Material: Metal Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material: Gold Precious Material: Gold Terminal and case surfaces gold Precious Material: Gold Source: Terminal and case surfaces gold Precious Material: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material Gold Voltage Rating And Cincludes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	1.1 watts
Storage Tempurature Range: -65.0 to 125.0 degrees celsius Features Provided: Hermetically sealed and burn in and thick film and hybrid Inclosure Material: Metal Inclosure Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 99006-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: Na Via	Operating Tempurature Range:
-65.0 to 125.0 degrees celsius         Features Provided:         Hermetically sealed and burn in and thick film and hybrid         Inclosure Material:         Metal         Inclosure Configuration:         Dual-in-line         Output Logic Form:         Transistor-transistor logic         Input Circuit Pattern:         12 input         Design Function And Quantity:         1 converter, digital to analog         Terminal Surface Treatment:         Gold         Voltage Rating And Type Per Characteristic:         18.0 volts power source         Precious Material         Precious Material         Gold         Terminal and case surfaces gold         Precious Material         Gold         Terminal Type And Quantity:         30 printed circuit         Sold         Support - Sold Document:         Solp inted circuit         She	-55.0 to 125.0 degrees celsius
Features Proved:   Hermetically sealed and burn in and thick film and hybrid   Inclosure Material:   Metal   Inclosure Configuration:   Dual-in-line   Output Logic Form:   Transistor-transistor logic   Input Circuit Pattern:   12 input   Design Function And Quantity:   1 converter, digital to analog   Terminal Surface Treatment:   Gold   Voltage Rating And Type Per Characteristic:   18.0 volts power source   Precious Material   Precious Material   Odd   Precious Material   Odd   Terminal and case surfaces gold   Precious Material   Ogold   Test Data Document:   9906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).   Terminal Type And Quantity:   30 printed circuit   Shelf Life:   N/a   Life:   N/a	Storage Tempurature Range:
Hermetically sealed and burn in and thick film and hybrid   Inclosure Material:   Metal   Inclosure Configuration:   Dual-in-line   Output Logic Form:   Transistor-transistor logic   Input Circuit Pattern:   12 input   Design Function And Quantity:   1 converter, digital to analog   Terminal Surface Treatment:   Gold   Voltage Rating And Type Per Characteristic:   18.0 volts power source   Precious Material   Material and case surfaces gold   Precious Material:   Gold   Gold   Terminal Type And Quantity:   30 printed circuit   Sourface Treatment:   Gold   Terminal and case surfaces gold   Precious Material:   Gold   Terminal Type And Quantity:   30 printed circuit   Shelf Life:   N'a   Life:   N'a	-65.0 to 125.0 degrees celsius
Inclosure Material: Metal Metal Inclosure Configuration: Dual-in-line Dutput Logic Form: Transistor-transistor logic Input Circuit Pattern: Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Codd Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: Gold Test Data Document: 2006-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Sheff Life: N/a Lift Of Measure: 	Features Provided:
Metal Inclosure Configuration: Dual-in-line Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: Tansistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	Hermetically sealed and burn in and thick film and hybrid
Transistor Configuration: Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: -	Inclosure Material:
Dual-in-line Output Logic Form: Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	Metal
Output Logic Form:         Transistor-transistor logic         Input Circuit Pattern:         12 input         Design Function And Quantity:         1 converter, digital to analog         Terminal Surface Treatment:         Gold         Voltage Rating And Type Per Characteristic:         18.0 volts power source         Precious Material And Location:         Terminal and case surfaces gold         Precious Material:         Gold         Sold         Precious Material:         Gold         Precious Material:         Ogold         Descuent:         Op inited circuit         Shelf Life:         N/a         Unit Of Measure:	Inclosure Configuration:
Transistor-transistor logic Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	Dual-in-line
Input Circuit Pattern: 12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Sheff Life: N/a Unit Of Measure:	Output Logic Form:
12 input Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Transistor-transistor logic
Design Function And Quantity: 1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Input Circuit Pattern:
1 converter, digital to analog Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	12 input
Terminal Surface Treatment: Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Design Function And Quantity:
Gold Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	1 converter, digital to analog
Voltage Rating And Type Per Characteristic: 18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Terminal Surface Treatment:
18.0 volts power source Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Gold
Precious Material And Location: Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: -	Voltage Rating And Type Per Characteristic:
Terminal and case surfaces gold Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	18.0 volts power source
Precious Material: Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	Precious Material And Location:
Gold Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure:	Terminal and case surfaces gold
Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Precious Material:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Gold
Terminal Type And Quantity: 30 printed circuit Shelf Life: N/a Unit Of Measure: 	Test Data Document:
30 printed circuit Shelf Life: N/a Unit Of Measure:	96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life: N/a Unit Of Measure: 	Terminal Type And Quantity:
N/a Unit Of Measure:	30 printed circuit
Unit Of Measure:	Shelf Life:
	N/a
	Unit Of Measure:
Demilitarization:	_
	Demilitarization:
Yes - demil/mli	Yes - demil/mli

## NSN 5962-01-256-8903

Digital-linear Microcircuit - Page 2 of 2

**Fiig:** A458a0

