## NSN 5962-01-257-2908

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-257-2908

0.360 inches  Body Height: 0.260 inches  Maximum Power Dissipation Rating: 3.1 watts  Operating Tempurature Range: -65.0/+150.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Monolithic  Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer  Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 22.0 volts power source  Test Data Document: Ferminal Type And Quantity: 4 pin Shelf Life: N/a Unit Of Measure:	Body Outside Diameter:
0.260 inches  Maximum Power Dissipation Rating: 3.1 waits  Operating Tempurature Range: -55.0/+150.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Monolithic  Monolithic  Inclosure Material: Metal  Inclosure Configuration: Can  Input Circuit Pattern: 1 input  Design Function And Quantity: 1 buffer  Case Outline Source And Designator: To-39 joint electron device engineering council  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 2.0 volts power source  Test Data Document:  96906-mil-sitd-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin  Shelf Life: N/a	0.360 inches
Maximum Power Dissipation Rating: 3.1 waits  Operating Tempurature Range: -55.0/+150.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Body Height:
3.1 watts  Operating Tempurature Range: -55.0/+150.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided: Monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	0.260 inches
Operating Tempurature Range: -55.0/+150.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Maximum Power Dissipation Rating:
-55.0/+150.0 degrees celsius  Storage Tempurature Range: -65.0/+150.0 degrees celsius  Features Provided:  Monolithic  Inclosure Material:  Metal  Inclosure Configuration: Can  Input Circuit Pattern: 1 input  Design Function And Quantity: 1 buffer  Case Outline Source And Designator: To-39 joint electron device engineering council  Terminal Surface Treatment: Solder  Voltage Rating And Type Per Characteristic: 2.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin  Shelf Life: N/a	3.1 watts
Storage Tempurature Range: -65.0+150.0 degrees celsius Features Provided: Monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Operating Tempurature Range:
Features Provided:  Monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	-55.0/+150.0 degrees celsius
Features Provided: Monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Storage Tempurature Range:
Monolithic Inclosure Material: Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	-65.0/+150.0 degrees celsius
Inclosure Material:  Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Features Provided:
Metal Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Monolithic
Inclosure Configuration: Can Input Circuit Pattern: 1 input Design Function And Quantity: 1 buffer Case Outline Source And Designator: To-39 joint electron device engineering council Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Inclosure Material:
Can Input Circuit Pattern:  1 input  Design Function And Quantity:  1 buffer  Case Outline Source And Designator:  To-39 joint electron device engineering council  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	Metal
Input Circuit Pattern:  1 input  Design Function And Quantity:  1 buffer  Case Outline Source And Designator:  To-39 joint electron device engineering council  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	Inclosure Configuration:
1 input  Design Function And Quantity:  1 buffer  Case Outline Source And Designator:  To-39 joint electron device engineering council  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	Can
Design Function And Quantity:  1 buffer  Case Outline Source And Designator:  To-39 joint electron device engineering council  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	Input Circuit Pattern:
1 buffer  Case Outline Source And Designator:  To-39 joint electron device engineering council  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic: 22.0 volts power source  Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity: 4 pin  Shelf Life: N/a	1 input
Case Outline Source And Designator:  To-39 joint electron device engineering council  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic: 22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	Design Function And Quantity:
To-39 joint electron device engineering council  Terminal Surface Treatment:  Solder  Voltage Rating And Type Per Characteristic:  22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	1 buffer
Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: 22.0 volts power source Test Data Document: 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Terminal Type And Quantity: 4 pin Shelf Life: N/a	Case Outline Source And Designator:
Solder  Voltage Rating And Type Per Characteristic:  22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	To-39 joint electron device engineering council
Voltage Rating And Type Per Characteristic:  22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity:  4 pin  Shelf Life:  N/a	Terminal Surface Treatment:
22.0 volts power source  Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity: 4 pin  Shelf Life: N/a	Solder
Test Data Document:  96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity: 4 pin  Shelf Life: N/a	Voltage Rating And Type Per Characteristic:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).  Terminal Type And Quantity: 4 pin  Shelf Life: N/a	22.0 volts power source
Terminal Type And Quantity: 4 pin Shelf Life: N/a	Test Data Document:
4 pin  Shelf Life: N/a	96906-mil-std-883  standard (includes industry or association standards, individual manufactureer standards, etc.).
Shelf Life: N/a	Terminal Type And Quantity:
N/a	4 pin
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
<del></del>	
Demilitarization:	Demilitarization:
Yes - demil/mli	Yes - demil/mli
Fiig:	Fiig:
	A458a0
A 450 - O	A458aU