NSN 5962-01-257-9636

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-257-9636 **Body Length:** 0.970 inches **Body Width:** 0.500 inches **Body Height:** 0.200 inches **Maximum Power Dissipation Rating:** 30.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **Features Provided:** Hybrid and hermetically sealed and burn in **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Quad 1 input **Design Function And Quantity:** 4 switch, field effect transistor **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -18.0 volts power source and 5.5 volts power source **Time Rating Per Chacteristic:** 60.00 nanoseconds propagation delay time, low to high level output and 40.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 03640-6134834-1 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:**

Fiig:

A458a0

Demilitarization: Yes - demil/mli