## NSN 5962-01-258-0789

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-258-0789 **Body Length:** 1.290 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** 0.210 inches **Maximum Power Dissipation Rating:** 1000.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **Features Provided:** Monolithic and high speed and hermetically sealed **Inclosure Material:** Ceramic and glass **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Metal oxide-semiconductor logic **Input Circuit Pattern:** 13 input **Criticality Code Justification:** Feat **Design Function And Quantity:** 1 converter, digital to analog **Case Outline Source And Designator:** D-3 mil-m-38510 **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** 18.0 volts power source **Special Features:** Item must comply with requirements of defense electronics supply center production standard no. L03765; for navy nuclear propulsion plant products only **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life:

--

N/a

**Unit Of Measure:** 

## NSN 5962-01-258-0789

Digital-linear Microcircuit - Page 2 of 2



Demilitarization:

No

Fiig:

A458a0