NSN 5962-01-258-3494

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-258-3494

Body Length: 0.785 inches **Body Width: Body Height:** 0.185 inches 500.0 milliwatts

Between 0.220 inches and 0.310 inches

Maximum Power Dissipation Rating:

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and monolithic and high speed

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

Hex 1 input

Design Function And Quantity:

6 schmitt trigger

Case Outline Source And Designator:

D-1 mil-m-38510

Current Rating Per Characteristic:

25.00 milliamperes forward current, peak total value not applicable

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

14 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

NSN 5962-01-258-3494

Digital Microcircuit - Page 2 of 2

Fiig: A458a0

