## NSN 5962-01-259-8915

Linear Microcircuit - Page 1 of 1



view Online at https://aerobasegroup.com/nsn/5962-01-259-6915
Body Length:
Between 1.980 inches and 2.020 inches
Body Width:
Between 0.582 inches and 0.596 inches
Body Height:
Between 0.084 inches and 0.104 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and monolithic and bipolar
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
29 input
Design Function And Quantity:
1 converter, digital to analog
Current Rating Per Characteristic:
20.00 milliamperes reverse current, dc absolute
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Capitance Rating Per Characteristic:
10.00 output picofarads
Time Rating Per Chacteristic:
35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
40 printed circuit
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

Yes - demil/mli Fiig:

A458a0