## NSN 5962-01-260-1937

Linear Microcircuit - Page 1 of 1



937

View Online at https://aerobasegroup.com/nsn/5962-01-260-19
Body Length:
Between 0.165 inches and 0.185 inches
Body Outside Diameter:
Between 0.305 inches and 0.370 inches
Maximum Power Dissipation Rating:
500.00 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Low noise and low drift and high performance
Inclosure Material:
Ceramic
Inclosure Configuration:
Can
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, general purpose
Case Outline Source And Designator:
To-99 joint electron device engineering council
Current Rating Per Characteristic:
75.00 nanoamperes peak forward surge current not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
22.0 volts power source
Time Rating Per Chacteristic:
300.00 nanoseconds rise transient
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
F::

Fiig:

A458a0