NSN 5962-01-260-1937

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-260-1937

Body Length:

Between 0.165 inches and 0.185 inches

Body Outside Diameter:

Between 0.305 inches and 0.370 inches

Maximum Power Dissipation Rating:

500.00 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Low noise and low drift and high performance

Inclosure Material:

Ceramic

Inclosure Configuration:

Can

Input Circuit Pattern:

Dual 2 input

Design Function And Quantity:

2 amplifier, operational, general purpose

Case Outline Source And Designator:

To-99 joint electron device engineering council

Current Rating Per Characteristic:

75.00 nanoamperes peak forward surge current not applicable

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

22.0 volts power source

Time Rating Per Chacteristic:

300.00 nanoseconds rise transient

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0