## NSN 5962-01-260-3890

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-260-3890

## **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and hermetically sealed and burn in and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 7 input **Design Function And Quantity:** 1 driver, high current **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Gold or solder or tin **Time Rating Per Chacteristic:** 5000.00 nanoseconds propagation delay time, low to high level output and 5000.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surface option gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). Shelf Life: N/a Unit Of Measure: **Demilitarization:** Yes - demil/mli

## Fiig:

---

A458a0