NSN 5962-01-260-3892

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-260-3892

| Body Length: |
|---|
| Between 0.770 inches and 0.825 inches |
| Body Width: |
| Between 0.480 inches and 0.520 inches |
| Body Height: |
| Between 0.120 inches and 0.150 inches |
| Maximum Power Dissipation Rating: |
| 795.0 milliwatts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hybrid and burn in and hermetically sealed |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Dual-in-line |
| Input Circuit Pattern: |
| 2 input |
| Design Function And Quantity: |
| 1 amplifier, sample/hold |
| Terminal Surface Treatment: |
| Gold or solder or tin |
| Precious Material And Location: |
| Terminal surfaces option gold |
| Precious Material: |
| Gold |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A458a0 |
| |