## NSN 5962-01-261-2297

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-261-2297

## **Body Length:** 1.280 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 1.2 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and programmable and bipolar **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 22 input **Design Function And Quantity:** 1 array, logic **Case Outline Source And Designator:** D-9 mil-m-38510 **Product Name:** Microcircuit, digital, memory, bipolar programmable logic **Voltage Rating And Type Per Characteristic:** -0.5 volts input and 7.0 volts input **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 24 printed circuit Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** Yes - demil/mli

## NSN 5962-01-261-2297

Digital Microcircuit - Page 2 of 2

**Fiig:** A458a0

