NSN 5962-01-261-4031

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-261-4031

| Body Length: | |
|-------------------------|-------------------------------------------------------------------------------------------------------------------|
| 1.035 inches | |
| Body Width: | |
| 0.530 inches | |
| Body Height: | |
| 0.190 inches | |
| Operating Tempura | ture Range: |
| -0.0/+70.0 degrees c | elsius |
| Storage Tempuratu | re Range: |
| -40.0/+125.0 degree | s celsius |
| End Application: | |
| 6625-01-215-6148 p | rocessor commu |
| Features Provided: | |
| Hermetically sealed | and w/clock and bidirectional and positive outputs |
| Inclosure Material: | |
| Metal | |
| Inclosure Configura | ation: |
| Dual-in-line | |
| Input Circuit Patter | n: |
| 10 input | |
| Design Function Ar | nd Quantity: |
| 2 flip-flop, edge trigg | jered, d-type |
| Terminal Surface T | reatment: |
| Solder | |
| Voltage Rating And | Type Per Characteristic: |
| 12.0 volts power sou | Irce |
| Time Rating Per Ch | acteristic: |
| 150.00 nanoseconds | propagation delay time, low to high level output and 150.00 nanoseconds propagation delay time, high to low level |
| output | |
| Terminal Type And | Quantity: |
| 18 printed circuit | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| Yes - demil/mli | |
| Fiig: | |
| A458a0 | |