

View Online at <https://aerobasegroup.com/nsn/5962-01-262-0449>

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.140 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

3-state output and monolithic and high speed and w/strobe

Inclosure Material:

Ceramic and glass

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

8 input

Design Function And Quantity:

1 selector and 1 multiplexer

Case Outline Source And Designator:

D-2 mil-m-38510

Current Rating Per Characteristic:

-20.00 milliamperes collector cutoff current, dc, with specified resistance between base and emitter and 20.00 milliamperes reverse current, dc

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

2.0 volts positive power supply span and 6.0 volts positive power supply span

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0