NSN 5962-01-262-1269



Digital Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-262-1269 **Body Length:** 0.528 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** 0.185 inches **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -55.0/+150.0 degrees celsius **Features Provided:** Low current and bipolar and hermetically sealed **Inclosure Material:** Ceramic and metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 driver, or **Terminal Surface Treatment:** Tin Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 750.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

Fiig:

A458a0