NSN 5962-01-262-2712

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-262-2712

Body Length:
0.350 inches
Body Width:
0.350 inches
Body Height:
0.100 inches
Maximum Power Dissipation Rating:
1.1 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Monolithic and bipolar and programmable
Inclosure Material:
Metal or plastic or ceramic
Inclosure Configuration:
Leaded chip carrier
Output Logic Form:
Bipolar metal-oxide semiconductor
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
C-2 mil-m-38510
Current Rating Per Characteristic:
12.00 milliamperes average forward current averaged over a full 60-hz cycle not applicable
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Memory Device Type:
Pal
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

NSN 5962-01-262-2712

Memory Microcircuit - Page 2 of 2

Fiig: A458a0

